

Cortical screws

Cortical screw 2.0

angle-stable; fully threaded;
depth stop; self tapping;
titanium  Internal hexagon



Cortical screw 2.4

angle-stable; fully threaded;
self tapping; titanium; TiOB®

 Six lobe



Cortical screw 2.4

fully threaded; self tapping;
titanium

 Six lobe



Pin 1.8 angle-stable; titanium;
TiOB®

 Six lobe



Cortical screw 2.7

fully threaded; self tapping;
titanium

 Internal hexagon



Cortical screw 2.7

angle-stable; fully threaded;
self tapping; titanium

 Internal hexagon



Cortical screw 2.7 SL10

fully threaded; flat head; self
tapping; titanium

 Six lobe



Cortical screw 2.7 SL10

angle-stable; fully threaded;
self tapping; titanium

 Six lobe



Cortical screw 3.5

fully threaded; self tapping;
titanium

 Internal hexagon



Contact details

If you are interested in
DISTAL RADIUS PLATES please feel
free to contact us or your local sales
representatives.



Königsee Implantate GmbH

OT Aschau | Am Sand 4
07426 Allendorf
Germany

export@koenigsee-implantate.de
+ 49 36738 498-560

All implants are available on
request as non-sterile packed
or sterile packed.



RADIUS PLATES

Titanium plates range



www.koenigsee-implantate.de

Radius plates

Almost all distal radius fractures can be treated surgically with our variable angle stable radius plate range. The anatomical shape of the plates in combination with the variable angular stability enables the stable treatment of extra- and intra-articular fractures.

Especially in intra-articular comminuted fractures, the variable angular stability offers an excellent prerequisite for positioning the screws to suit the individual fracture situation. the individual fracture situation.

Distal radius plates 2.7 vas

variable angle-stable; plate thickness 2.0 mm; for screws Ø 2.7 mm; width shaft 10 mm; plates for right and left sides; titanium



- narrow**
- 5 head holes
 - shaft holes 2 – 13
 - width head 23 mm
 - length 43 – 136 mm



- broad**
- 7 head holes
 - shaft holes 2 – 13
 - width head 27 mm
 - length 43 – 136 mm

Distal radius plates 2.4

variable angle-stable; plate thickness 1.8 mm; for screws Ø 2.4 and Pins Ø 1.8 mm; width shaft 10 mm; plates for right and left sides; titanium



- narrow**
- 7 head holes
 - shaft holes 2 – 12
 - width head 23 mm
 - length 46 – 131 mm



- broad**
- 9 head holes
 - shaft holes 2 – 12
 - width head 28 mm
 - length 46 – 131 mm



- Watershed**
- 7 head holes
 - shaft holes 3 | 4
 - width head 23 mm
 - length 50 | 59 mm



Distal radius plates 2.0/3.5

angle-stable; plate thickness head 2.0 mm; plate thickness shaft 1.5 mm; for screws Ø 2.0/3.5 mm; width shaft 10 mm; plates for right and left sides; titanium



- dorsal**
- 4 head holes
 - 3 shaft holes
 - width head 28 mm
 - length 63 mm



- dorsal broad**
- 5 head holes
 - 3 shaft holes
 - width head 33 mm
 - length 63 mm



- palmar**
- 6 head holes
 - shaft holes 3 | 5
 - width head 25 mm
 - length 50 | 67 mm



- palmar LH middle**
- 6 head holes
 - 3 shaft holes
 - width head 25 mm
 - length 50 mm

